

INOcell® HASCHUR 45° – VOLUMENTABELLE (cm³/m²)

Cliché	L/cm	Volumen (cm ³ /m ²)	Volumen in cm ³ /m ²	
			min. ←	→ max.
54	320	3,0–5,0	2,0	5,0
	300	4,0–6,0	3,0	6,0
	280	4,0–8,0	4,0	8,0
	260	5,0–10,0	5,0	10,0
42 Fläche / Strich	220	6,0–11,0	6,0	11,0
	200	7,0–12,0	7,0	12,0
	180	8,0–14,0	8,0	14,0
	160	9,0–16,0	9,0	16,0
	140	10,0–18,0	10,0	18,0
Fläche / Weiß Standard	120	11,0–20,0	11,0	20,0
	100	12,0–22,0	12,0	22,0
	80	13,0–25,0	13,0	25,0
	60	14,0–28,0	14,0	28,0
	45	15,0–35,0	15,0	35,0

VOLUMEN TOLERANZEN

Volumen bis 3 cm³/m² / ±4%

Volumen von 3–6 cm³/m² / ±5%

Volumen über 6 cm³/m² / ±6%

POLISHBACK STANDARD

UV: 9–15%

STD: 30–50%

W&H: 60–70%

LINIENZAHL TOLERANZEN

±10 Linien